



Fujitsu Production Scanner Matrix

Production Scanner Model		Low-Volume Production Scanners				Mid-Volume Production Scanners	
		fi-6670	fi-6670A	fi-6770	fi-6770A	fi-4860C2-VRS	fi-5900C
							
Part #		PA03576-B505	PA03576-B535	PA03576-B005	PA03576-B035	PA03296-B075	PA03450-B005
Daily Duty Cycle (Pages per day)		Up to 15,000	Up to 15,000	Up to 15,000	Up to 15,000	Up to 10,000	Up to 100,000
Landscape (Monochrome, grayscale or color)	Speed @200DPI	90ppm/180ipm	90ppm/180ipm	90ppm/180ipm	90ppm/180ipm	54ppm/64ipm	120ppm/240ipm
	Speed @300DPI	80ppm/160ipm	80ppm/160ipm	80ppm/160ipm	80ppm/160ipm	50ppm/100ipm	120ppm/240ipm
Portrait (Monochrome, grayscale or color)	Speed @200DPI	70ppm/140ipm	70ppm/140ipm	70ppm/140ipm	70ppm/140ipm	63ppm/125ipm	100ppm/200ipm
	Speed @300DPI	60ppm/120ipm	60ppm/120ipm	60ppm/120ipm	60ppm/120ipm	48ppm/90ipm	100ppm/200ipm
Grayscale		8 Bit 256 Levels	8 Bit 256 Levels	8 Bit 256 Levels	8 Bit 256 Levels	8 Bit 256 Levels	8 Bit 256 Levels
Simplex/Duplex		Duplex	Duplex	Duplex	Duplex	Duplex	Duplex
Flatbed Max.		N/A	N/A	(11x17)	(11x17)	N/A	N/A
Resolution	Output	50-600dpi	50-600dpi	50-600dpi	50-600dpi	100-400dpi	50-600dpi
	Optical	600dpi	600dpi	600dpi	600dpi	400dpi	600dpi
ADF (Paper)	ADF Capacity	200 Sheet	200 Sheet	200 Sheet	200 Sheet	250 & 500	500 Sheet
	ADF Min.	A8 (2 x 3)	A8 (2 x 3)	A8 (2 x 3)	A8 (2 x 3)	(2.9x2.9)	2.1" x 2.9"
	ADF Max.	(11x17)	(11x17)	(11x17)	(11x17)	A3 (11.7x17)	12" x 17"
Interface		Ultra SCSI (50M) / USB 2.0 / third party slot	Ultra SCSI (50M) / USB 2.0 / Ultra SCSI (60M) CGA / USB 2.0 CGA	Ultra SCSI (50M) / USB 2.0 / third party slot	Ultra SCSI (50M) / USB 2.0 / Ultra SCSI (60M) CGA / USB 2.0 CGA	VRS Ultra Wide SCSI (68M)	Ultra Wide SCSI & USB 2.0 / VRS Ultra Wide SCSI & VRS USB 2.0 / third party slot
Color		24 Bit	24 Bit	24 Bit	24 Bit	24 Bit	24 Bit
Image Enhancement	Image Enhancement	VRS 4.2 Professional	Hardware assisted VRS 4.2 Professional ³	VRS 4.2 Professional	Hardware assisted VRS 4.2 Professional ³	Hardware assisted VRS 4.1 Professional ³	Hardware assisted VRS 4.1 Professional ³
	Options	VRS 4.2 Professional CGA and Software IPC	Software IPC option ² (PN# PA43402-C22903)	VRS 4.2 Professional CGA and Software IPC	Software IPC option ² (PN# PA43402-C22903)	Software IPC option ² (PN# PA43402-C22903)	Software IPC option ² (PN# PA43402-C22903)
Background		Switchable Black / White (ADF)	Switchable Black / White (ADF)	Switchable Black / White (ADF)	Switchable Black / White (ADF)	Switchable Black / White (ADF)	Switchable Black / White (ADF)
Drivers / Software Incl.		Twain, ISIS, VRS 4.2 Professional, Adobe Acrobat 8.0 Std, ScandAll PRO with SharePoint connect	Twain, ISIS, Hardware-assisted VRS 4.2 Professional CGA, Adobe Acrobat 8.0 Std, ScandAll PRO with SharePoint connect	Twain, ISIS, VRS 4.2 Professional, Adobe Acrobat 8.0 Std, ScandAll PRO with SharePoint connect	Twain, ISIS, Hardware-assisted VRS 4.2 Professional CGA, Adobe Acrobat 8.0 Std, ScandAll PRO with SharePoint connect	Twain, ISIS, Hardware-assisted VRS 4.1 Professional, Adobe Acrobat 7.0 Std, ScandAll 21	Twain, ISIS, Hardware-assisted VRS 4.1 Professional, Adobe Acrobat 7.0 Std, ScandAll 21
Hardware Incl.		USB 2.0 Cable	USB 2.0 Cable	USB 2.0 Cable	USB 2.0 Cable	Adrenaline 650i & SCSI Cable	USB 2.0 Cable
Endorser/ Imprinter Options		40 Character Max Post Scan, Back side of Document	40 Character Max Post Scan, Back side of Document	N/A	N/A	40 Character Max Pre-scan, Front side (PN# CG01000-498801) & 40 Character Max Post scan, Back side (PN# CG01000-522501)	40 Character Max Pre-scan, Front side (PN# CG01000-591501) & 40 Character Max Post scan, Back side (PN# CG01000-519601)
Color Dropout		Software Color Dropout	Software Color Dropout	Software Color Dropout	Software Color Dropout	Std. R/G/B Color Dropout	Customized Color Dropout plus Std. R/G/B (selectable)
Long Document Scanning	ISIS Driver	120"	120"	120"	120"	34" ⁴	34" ⁴
	TWAIN Driver	120"	120"	120"	120"	34" ⁴	34" ⁴
Physical Dimensions	Dimensions (HxWxD)	11.5x25.2x16.9	11.5x25.2x16.9	13.5x27.2x19.7	13.5x27.2x19.7	20.6x20.5x17	20x21x21
	Weight (LBS)	44	44	77.2	77.2	100	110.4
Warranty¹		3 months on-site	3 months on-site	3 months on-site	3 months on-site	3 months on-site	3 months on-site

¹ All on-site warranties are based on next day service. Some Cities have same day service on the fi-5900C. Call your supplier for details

² IPC Functions: Dynamic thresholding, Spot noise removal, OCR smoothing, Filtering, Automatic separation photo/text, Image emphasis, Reverse image, Zooming 25%-200% by 1% steps,

Outline extraction, Mirror image, Background removal.

³ VirtualReScan™ Professional (VRS) Functions: Automatic color detection, Background saturation, Content-based rotation, Blank page deletion, White background cropping and Deskew, and Advanced Clarity

⁴ Monochrome support only. Maximum resolution varies from 300-400dpi. Long document scanning may not be supported by third-party software.

Long document scanning is supported by ScandAll utility. Please refer to long document scanning matrix for specifics and limitations.